

# PHS Service Grommets

PHS service grommets are made from a strong and flexible EPDM. They're specifically designed for quick and secure sealing of pipes penetrating both the internal airtight vapour control layer & external waterproof/windtight layer.

PHS grommets provide a tight, flexible fit that prevents the uncontrolled flow of water vapour and air, allowing for greater airtight levels and prevention of interstitial condensation.

PHS grommets are bonded to the appropriate substrate with PHS Argo tape or another suitable universal joining tape.

## Application

Before application of PHS service grommets, ensure that the application area is clean, dry, grease and dust free.

Adhesion to frozen surfaces isn't possible and apply only in the appropriate application temperature

PHS Argo tape provides a permanent bond between the grommet and substrate. If bonding to MDF, precondition the surface with a suitable primer to ensure the best possible bond.



## Grommets Sizes

4-8mm	50mm diameter	1mm thickness/ round grommet
25-32mm	98mm diameter	1mm thickness/ round grommet
50-60mm	150mm diameter	1.5mm thickness/ square grommet
100-110mm	245mm diameter	1.5mm thickness/ square grommet
120-130mm	256mm diameter	1.5mm thickness/ round grommet
150-165mm	280mm diameter	1.5mm thickness/ round grommet

## Technical Data

Material	EPDM
Temperature Resistance	-30C to +100C
Application Temperature	-10C to +40C
Life Expectancy	60 years +
Usage	Internal & External
Colour	Black