

# **PHS Felt Collars**

Poorly finished penetrations in the airtight membrane and the vapor control layer can lead to rapid damage of the adjoining building elements and an unnecessary loss of heat and energy via the building envelope. Airtight Grommets not only reduce the heat loss of your house, but also save heat energy and prevent damage due to humidity.

What makes Airtight Felt Collars so special? The various laminations and diameters allow you to seal installation passages individually according to your special needs. The felt collars consist of flexible EPDM-rubber bonded with a self-adhesive pad, carrier material (base) Tyvek with an age resistent layer of acrylate adhesive.

### **Application**


- The surfaces must be dust-free and free of grease as well as dry and stable.
- Ensure there is a tight fit between the EPDM sleeve and the service carrier.
- The Tyvek self-adhesive surface liner should be removed and the felt collar fitted to the substrate.

## **Important Notes**

- The sleeves are delivered talc powdered. If there is insufficient gliding ability, please use the provided talc powder, in order to rework the inner sleeve or the cable.
- The self-adhesive acrylate sleeves are safe and permanently moisture-proof. They are also suitable for gas barriers. Adhesive surfaces include wood fibreboards, OSB-boards, vapour barriers or vapour locks and sarking membrane.
- Finally you should pre-treat some surfaces with PHS Primer.
  The surfaces must be dust-free and free of grease as well as dry and stable.

#### Technical Data

Shelf Life / storage	Cool and dry
Temperature Resistance	-20C to +100C
Application Temperature	Above -5C
UV resistance	Excellent
Adhesive Strength	>35 / N25mm
Tear Strength	>150 / N25mm
•	



#### Grommets Sizes

Collar Type	D1	GD22	RGD50
Number of bushings	1 line cuff	1 line cuff	1 line cuff
Dimensions of adhesive collar	150x150mm	150x150mm	230x230mm
External diameter	4-8mm	25-32mm	50-70mm
Number per box	10pcs	10pcs	4pcs

Collar Type	RGD100	FRGD100	RGD25
Number of bushings	1 line cuff	1 line cuff	1 line cuff
Dimensions of adhesive collar	320x320mm	350x350mm	230x230mm
External diameter	100-110mm	100-125mm	125-135mm
Number per box	10pcs	4pcs	4pcs

Ireland / Passive House Systems P31 W950, Ballincollig, Cork, Ireland tel. (+353) 021 487 2664 www.passivehousesystems ie

UK / Passive House Systems CM16 6th, Epping, Essex, UK tel. (+44) 0333 880 2347 www.passivehousesystems.co.ul Passive House Systems products are used by a very diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement. All data and recommendations contained in this Technical Datasheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liabiolity. We reseve the right to change the technical specification without prior notice. Samples are available free of charge, our sales team are available to help support all technical specifications for our products.