

# PHS Inspection Door

The PHS Timber Inspection Door is a real winner when it comes to the prevention of heat loss with its 80mm insulation and air impermeable seals.

Ideal for quickly and safely accessing storage space behind, for example, knee wall attic spaces. Supplied with a 2-point lock and a short reach operating pole for ease of use.

## Advantages

- Well insulated (80mm of insulation).
- An air tight assembly (Class 4 to EN1026).
- Secured with a 2-point locking mechanism.
- Quick and easy fitting.
- Aesthetically adaptable with a paintable white lid finish.
- Outer frame air tightness kit optional.
- Easy to use with a short locking pole.

## Dimensions

- 590mm x 590mm.
- 690mm x 690mm.
- 790mm x 540mm.
- 1090mm x 550mm.

## Technical Data

Opening	600mm x 600mm , 700mm x 700mm , 800mm x 550mm , 1100mm x 550mm
U-Value	0.4 W/m <sup>2</sup> .K; Ref: ISO 6949
Air Tightness	Class 4; Ref: EN1026



**\*A poorly insulated and draught inspection door will result in significant heat loss and potential moisture damage in your attic space.**

**\*Always insist on a quality inspection door and ensure it is well fitted.**

Passive House Systems IE  
P31 W950, Ballincollig, Cork, Ireland  
tel. (+353) 021 4872664  
[www.passivehousesystems.ie](http://www.passivehousesystems.ie)

Passive House Systems UK  
CM16 6th, Epping, Essex, UK  
tel. (+44) 0333 880 2347  
[www.passivehousesystems.co.uk](http://www.passivehousesystems.co.uk)

Passive House Systems products are used by diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement.

All data and recommendations contained in this Technical Datasheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. Our sales team are available to help support all technical specifications for our products.