

PHS Primer

Adhesive PHS Primer paint is a dispersion-based polyacrylate, with a low to medium viscosity prime coat. Designed to prepare rough and sandy application surfaces for airtightness tape adhesion.

Application

- Apply PHS Primer on the surface to be bonded.
- Let the primer dry well before further processing of the surface.
- The applied primer should feel mostly dry.
- Apply several times on difficult substrates, if necessary, and allow to dry well each time.
- Apply the adhesive tape on the treated surface and press firmly at once. Observe the instructions for use of the respective adhesive tape.

Advantages

- Ideal for: wooden construction materials, masonry and concrete.
- Easy and even to apply.
- Quick-drying.

Consumption Value (per 1kg)

- Stone/concrete approx 12m².
- Fire boards approx 6m².



Technical Data

Basis	Polyacrylate dispersion
Temperature ranging after application	-20°C to +0°C
Shelf Life	in unopened can, 12 months

Passive House Systems IE
P31 W950, Ballincollig, Cork, Ireland
tel. (+353) 021 4872664
www.passivehousesystems.ie

Passive House Systems UK
CM16 6th, Epping, Essex, UK
tel. (+44) 0333 880 2347
www.passivehousesystems.co.uk

Passive House Systems products are used by diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement.

All data and recommendations contained in this Technical Datasheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. Our sales team are available to help support all technical specifications for our products.