


# PHS Reflecta

PHS Reflecta Reflective Aluminium tape – a durable, flexible and effective windtight & airtight reflective membrane joining tape.

It ensures a long-lasting bond with common construction substrates. PHS Reflecta – Reflective Aluminium Tape provides an effective airtight seal at joints and penetrations. It also allows for sequencing of more vapour permeable materials externally when used internally. Combined with its metallised, low emissivity surface, Reflecta reduces convection heat loss. It also makes it the ideal solution for jointing and sealing foil faced insulation boards and reflective membranes. When used to tape foil faced insulation externally, Reflecta achieves a windtight layer that prevents wind-washing, increasing the thermal performance of insulation. Reflecta has a high tear, water and aging resistance and high durability.

Reflecta is ideal for joining vapour control membranes, specifically reflective membranes. It helps to reduce heat loss associated with air leakage and increases the energy performance of the building envelope, while also reducing the risk of interstitial condensation.



## Application

- Reflecta tape provides a simple, airtight, self adhesive and reflective surface. When applying Reflecta tape, a clean and dry surface is required.
- We recommend using a suitable cleaner to prepare the surface, this will clear all dust and grease away, and create a good quality application surface. Measure out the Reflecta tape against the application area or measure the area to get a view of how much reflective tape is needed. This will help during application and minimize the chance of waste material.
- The tape can be cut easily with a utility knife. To apply, peel away the backing layer and proceed to stick it to the application area, while running your hand against the material, pressing it down. By slowly applying the reflective tape to the application area like this, you can be sure of a good quality application with minimal air bubbles or creases in the material. Once applied, the Reflective tape will create a good quality, airtight and vapour control layer.

## Technical Data

Backing Thickness	36micron
Peel Adhesion	18N/25mm
Tack Rolling Ball	20cm
Tensile Strength	45N/25mm
Elongation	3%
Reflectivity	97%
Emissivity	0.03
Tear Strength	226.4N/25mm
Service Temperature	-10°C to +120°C
Applying Temperature	10°C to 40°C

Passive House Systems IE  
P31 W950, Ballincollig, Cork, Ireland  
tel. (+353) 021 4872664  
[www.passivehousesystems.ie](http://www.passivehousesystems.ie)

Passive House Systems UK  
CM16 6th, Epping, Essex, UK  
tel. (+44) 0333 880 2347  
[www.passivehousesystems.co.uk](http://www.passivehousesystems.co.uk)

Passive House Systems products are used by diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement.

All data and recommendations contained in this Technical Datasheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. Our sales team are available to help support all technical specifications for our products.