







PHS DELUX Loft Stairs

The **PHS DELUX Loft Stairs** is a high quality folding attic ladder with a spring counterbalance mechanism for ease of operation. The **PHS DELUX Loft Stairs** is manufactured to the highest quality standards from top grade Beech and Pine woods with deep, non-slip threaded steps, robust spring and latch systems for effortless counterbalance operation and a single point lock with long reach operating pole.



Features & Benefits

-  Beech stairs with a Pine wood frame.
-  White hatch.
-  Stile ends for stable fixing and floor protection.
-  Safety handrail.
-  Airtight peripheral seal.
-  Fully assembled for quick ceiling installation.
-  Non-slip threads set flush with the ladder steps.
-  Easy & quick installation.
-  Single Compression Lock.



Technical Data

PHS DELUX Loft Stairs	
Insulation Thickness:	26mm
U-value:	0.83W /m ² K
Certification:	EN14975:2006+A1:2010
Airtightness Level:	Class 4 (EN 1026), i.e. 0100≤0.1 m ³ /hr.m ²
Locking Mechanism Aesthetics:	1 point with seal compression.
Construction Type:	A white lid finish
Hand Rail Safety:	As standard
Load Bearing Capacity:	150kg
Dimensions (Unfolded):	1190mm x 590mm x 2800mm (Art: AR9051B) 1130mm x 540mm x 2800mm (Art: AR9051C)

Made with quality craftsmanship and superior finishing.



EN14975:2006+A1:2010

Ireland: Passive House Systems
P31 W950, Ballincollig, Cork, Ireland
Tel. (+353) 021487 2664
www.passivehousesystems.ie

UK: Passive House Systems
CM16 6th, Epping, Essex, UK
Tel. (+44) 0333 880 2347
www.passivehousesystems.co.uk

Passive House Systems products are used by a very diverse customer base for a wide range of technical and industrial applications. The demands made on our products vary considerably from application to application. We strongly advise users to test the products suitability for their own particular requirement. All data and recommendations contained in this Technical Datasheet are based on our own test results and practical experience and are aimed at helping customers select the appropriate product. This information is provided without liability. We reserve the right to change the technical specification without prior notice. Samples are available free of charge. our sales team are available to help support all technical specifications for our products.